# Lithium Iron Phosphate (LiFePO4) Battery

### LFP12.8V135AH-FT-BT

#### 12.8V135AH FT 1728Wh

### Features of LiFePO4 Battery

### **Longer Cycle Life**

LiFeP04 batteries have over 5 times the cycle life of SLA batteries.

#### High Power & Light weight

LiFeP04 batteries have twice the performance of SLA batteries while being half the weight.

### Intelligent management control


Power Lithium intelligent BMS monitors battery cells to ensure batteries work safely and perform at full potential.

### Lower Self-discharge rate

Lower self-discharge rate mean batteries can be stored for longer when compared to SLA.



# **Physical Dimension**



### **Applications**

- Caravan, RV, camping
- •UPS (replacement of SLA batteries)
- •Marine, golf cart
- Solar, wind system
- PV ,solar light

# Electrical Characteristics

Standard Charge

Standard Discharge

Chemistry	LiFePO4
Nominal Voltage	12.8V
Nominal Capacity	135Ah (C5,25°C)
Energy	1728Wh
Internal Resistance	≤12 mΩ
Cycle Life	>2000 cycles @1C 100%DOD
Months Self Discharge	<3%
Efficiency of Charge	100% @0.5C
Efficiency of Discharge	96-99% @1C
Charge Voltage	14.6±0.2V
Charge Mode	0.2C to 14.6V, then 14.6V, charge current to 0.02C (CC/CV)
Charger Current	67.5A
Max. Charge Current	135A
Charge Cut-off Voltage	15.6V±0.2V
Rated Discharge Current	67.5A
Max Discharge Current	135A
Max. Pulse Current	405A(<3s)
Discharge Cut-off Voltage	10V
Charge Temperature	0 °C to 45 °C (32Fto 113F) @60±25% Relative Humidity
Discharge Temperature	-20 °C to 60 °C (-4F to 140F) @60±25% Relative Humidity
Storage Temperature	0 °C to 40 °C (32Fto 104F) @60±25% Relative Humidity
Water Dust Resistance	IP65
BMS	4 Series / 4 Parallel - Bluetooth Enabled
Case	ABS
Dimensions (in./mm.)	395 x 110 x 286 mm

14.8 kg M8





Mechanical





Weight (lbs./kg.)

Terminal









# TECHNOLOGY

# LifePO4 LITHIUM ION


### POWER LITHIUM BATTERIES


Lithium Iron Phosphate (LiFePO4) Battery

LFP12.8V135AH-FT-BT

12.8V135AH FT 1728Wh

## Different Rate Discharge Curve(25℃) 14.0 13.2 Voltage (V) 12.4 10.8 10.0 0.10 0 20min 40min 60min 5h 10h State of Charge Curve(0.5C, 25°C) 15.0 14.5







**Different Temperature Self Discharge Curve** 

